

AROMALAND, INC.

1326 Rufina Circle

Santa Fe, NM 87507

800-933-5267

505-438-0402 505-670-7072 (24 hr)

MATERIAL SAFETY DATA SHEET – STEAMIST ENERGIZE ESSENTIAL OIL BLEND

IDENTIFICATION

LABEL NAME: STEAMIST ENERGIZE ESSENTIAL OIL BLEND

BOTANICAL NAME N/A

SYNONYMS: N/A

COMPONENTS:

<u>Essential Oil</u>	<u>Botanical Name</u>	<u>CAS NUMBER</u>	<u>Origin</u>
Cinnamon	<i>Cinnamomum zeylanicum</i>	8015-91-6	Sri Lanka
Ginger	<i>Zingiber officinalis</i>	8007-08-7	India
Grapefruit	<i>Citrus paradisi</i>	8016-20-4	USA
Lemon	<i>Citrus limonum</i>	8008-56-8	Italy
Lemongrass	<i>Cymbopogon flexuosus</i>	8007-02-1	India
Mandarin Orange	<i>Citrus reticulata var mandarin</i>	8008-31-9	Italy
Orange (Sweet)	<i>Citrus sinensis</i>	8008-57-9	USA
Rosemary	<i>Rosmarinus officinalis</i>	8000-25-7	Spain

PHYSICAL DATA

APPEARANCE: Pale yellow to yellow clear liquid

ODOR: Spicy citrus scent

SPECIFIC GRAVITY: 0.8600 to 0.8850 REFRACTIVE INDEX: NDA

MELTING POINT: NDA BOILING POINT:

VAPOR DENSITY: NDA VAPOR PRESSURE: NDA

SOLUBILITY IN WATER: INSOLUBLE EVAPORATION RATE: NDA

FIRE, EXPLOSION AND REACTIVITY

FLASHPOINT: 48° C

STABILITY: STABLE UNDER NORMAL CONDITIONS

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0 PERSONAL PROTECTION: 1

4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = NO SIGNIFICANT HAZARD

SPECIAL FIRE FIGHTING PROCEDURE/UNUSUAL FIRE AND EXPLOSION HAZARDS: *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

NONE KNOWN. USE SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING

HAZARDOUS COMBUSTION/DECOMPOSITION PRODUCT:

BURNING PRODUCES CARBON MONOXIDE AND CARBON DIOXIDE

HAZARDOUS POLYMERIZATION PRODUCT:

WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:

ELEVATED TEMPERATURES ABOVE 60 DEGREES CENTIGRADE, AVOID STRONG OXIDIZING AGENTS

PROTECTION INFORMATION: *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

RESPIRATORY PROTECTION: NOT USUALLY NECESSARY, BUT APPROVED RESPIRATOR CAN BE USED IF DESIRED

EYE PROTECTION: USE SPLASH GOGGLES

MATERIAL SAFETY DATA SHEET - STEAMIST ENERGIZE ESSENTIAL OIL BLEND, CONT.

SKIN PROTECTION: USE CHEMICAL RESISTANT GLOVES
VENTILATION: LOCALIZED EXHAUST CAN BE USED TO REMOVE VAPORS
OTHER: EYE WASH STATION AND SAFETY SHOWER RECOMMENDED IN AREA

OCCUPATIONAL EXPOSURE LIMITS *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

THRESHOLD LIMIT VALUE (TLV): N/A
EFFECTS OF OVEREXPOSURE: REDNESS OF SKIN AND/OR EYES
OSHA PERMISSIBLE EXPOSURE LIMIT (PEL): N/A
HAS SUBSTANCE BEEN LISTED AS A CARCINOGEN: NO

EMERGENCY AND FIRST AID PROCEDURES *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

INHALATION: REMOVE TO FRESH AIR
EYE CONTACT: FLUSH WATER FOR 15 MINUTES
SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER
INGESTION: DRINK WATER OR MILK TO DILUTE, CONTACT POISON CONTROL

HEALTH HAZARD INFORMATION *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

MAY BE IRRITATING TO SKIN AND EYES
VAPOR MAY BE IRRITATING TO THROAT AND LUNGS
BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE ANESTHETIC EFFECTS
REPEATED CONTACT MAY CAUSE ALLERGIC DERMATITIS

SPILLS LEAKS AND DISPOSAL PROCEDURE *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

IF MATERIAL SHOULD BE SPILLED OR RELEASED: ELIMINATE FLAMES AND SOURCES OF IGNITION, WIPE UP SMALL SPILLS WITH A CLOTH, LARGER SPILLS USE POROUS ABSORBENT

WASTE DISPOSAL METHODS: FOLLOW STATE, LOCAL AND FEDERAL LAWS

HANDLING AND SHIPPING PROCEDURES *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

HANDLE ACCORDING TO GOOD SAFETY PROCEDURES AVOIDING UNNECESSARY EXPOSURE.
STORE IN FULL CLOSED CONTAINERS AWAY FROM HEAT, LIGHT AND SOURCES OF IGNITION.
STORE IN COOL AREA.

THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET WAS OBTAINED FROM CURRENT AND RELIABLE SOURCES. THIS DATA IS SUPPLIED WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY. IT IS THE USER'S RESPONSIBILITY TO DETERMINE SAFE CONDITIONS FOR USE OF THIS PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE OR EXPENSE RESULTING FROM IMPROPER USE OF THIS PRODUCT.