

# AROMALAND, INC.

1326 Rufina Circle

Santa Fe, NM 87507

800-933-5267

505-438-0402 505-670-7072 (24 hr)

## MATERIAL SAFETY DATA SHEET – STEAMIST RENEW ESSENTIAL OIL BLEND

### IDENTIFICATION

LABEL NAME: STEAMIST RENEW ESSENTIAL OIL BLEND

BOTANICAL NAME N/A

SYNONYMS: N/A

COMPONENTS:

| <u>Essential Oil</u> | <u>Botanical Name</u>         | <u>CAS NUMBER</u> | <u>Origin</u> |
|----------------------|-------------------------------|-------------------|---------------|
| Cedarwood            | <i>Juniperus virginiana</i>   | 8000-27-9         | USA           |
| Frankincense         | <i>Boswellia carterii</i>     | 8016-36-2         | Oman          |
| Geranium             | <i>Pelagonium graveleons</i>  | 8000-16-2         | Egypt         |
| Lavender             | <i>Lavendula angustifolia</i> | 8000-28-0         | Bulgaria      |
| Marjoram             | <i>Thymus mastichina</i>      | 8015-33-9         | Spain         |
| Orange (Sweet)       | <i>Citrus sinensis</i>        | 8008-57-9         | USA           |
| Marjoram             | <i>Thymus mastichina</i>      | 8015-33-9         | Spain         |

### PHYSICAL DATA

APPEARANCE: Pale yellow to yellow clear liquid

ODOR: Sweet, slightly camphoraceous with balsamic and light citrus undertone

SPECIFIC GRAVITY: NDA REFRACTIVE INDEX: NDA

MELTING POINT: NDA BOILING POINT:

VAPOR DENSITY: NDA VAPOR PRESSURE: NDA

SOLUBILITY IN WATER: INSOLUBLE EVAPORATION RATE: NDA

### FIRE, EXPLOSION AND REACTIVITY

FLASHPOINT: 49° C

STABILITY: STABLE UNDER NORMAL CONDITIONS

**HAZARDOUS MATERIALS IDENTIFICATION SYSTEM** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

HEALTH: 1 FLAMMABILITY: 2 REACTIVITY: 0 PERSONAL PROTECTION: 1

4 = EXTREME 3 = HIGH 2 = MODERATE 1 = SLIGHT 0 = NO SIGNIFICANT HAZARD

**SPECIAL FIRE FIGHTING PROCEDURE/UNUSUAL FIRE AND EXPLOSION HAZARDS:** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

NONE KNOWN. USE SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING

**HAZARDOUS COMBUSTION/DECOMPOSITION PRODUCT:**

BURNING PRODUCES CARBON MONOXIDE AND CARBON DIOXIDE

**HAZARDOUS POLYMERIZATION PRODUCT:**

WILL NOT OCCUR

**CONDITIONS AND MATERIALS TO AVOID:**

ELEVATED TEMPERATURES ABOVE 60 DEGREES CENTIGRADE, AVOID STRONG OXIDIZING AGENTS

**PROTECTION INFORMATION:** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

RESPIRATORY PROTECTION: NOT USUALLY NECESSARY, BUT APPROVED RESPIRATOR CAN BE USED IF DESIRED

EYE PROTECTION: USE SPLASH GOGGLES

MATERIAL SAFETY DATA SHEET - STEAMIST RENEW ESSENTIAL OIL BLEND, CONT.

SKIN PROTECTION: USE CHEMICAL RESISTANT GLOVES  
VENTILATION: LOCALIZED EXHAUST CAN BE USED TO REMOVE VAPORS  
OTHER: EYE WASH STATION AND SAFETY SHOWER RECOMMENDED IN AREA

**OCCUPATIONAL EXPOSURE LIMITS** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

THRESHOLD LIMIT VALUE (TLV): N/A  
EFFECTS OF OVEREXPOSURE: REDNESS OF SKIN AND/OR EYES  
OSHA PERMISSIBLE EXPOSURE LIMIT (PEL): N/A  
HAS SUBSTANCE BEEN LISTED AS A CARCINOGEN: NO

**EMERGENCY AND FIRST AID PROCEDURES** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

INHALATION: REMOVE TO FRESH AIR  
EYE CONTACT: FLUSH WATER FOR 15 MINUTES  
SKIN CONTACT: REMOVE CONTAMINATED CLOTHING AND WASH WITH SOAP AND WATER  
INGESTION: DRINK WATER OR MILK TO DILUTE, CONTACT POISON CONTROL

**HEALTH HAZARD INFORMATION** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

MAY BE IRRITATING TO SKIN AND EYES  
VAPOR MAY BE IRRITATING TO THROAT AND LUNGS  
BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE ANESTHETIC EFFECTS  
REPEATED CONTACT MAY CAUSE ALLERGIC DERMATITIS

**SPILLS LEAKS AND DISPOSAL PROCEDURE** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

IF MATERIAL SHOULD BE SPILLED OR RELEASED: ELIMINATE FLAMES AND SOURCES OF IGNITION, WIPE UP SMALL SPILLS WITH A CLOTH, LARGER SPILLS USE POROUS ABSORBENT

WASTE DISPOSAL METHODS: FOLLOW STATE, LOCAL AND FEDERAL LAWS

**HANDLING AND SHIPPING PROCEDURES** *As required by the Occupational Health and Safety Administration (OSHA), the target audience for information in a MSDS is the occupation worker who may be exposed to manufacturing materials at work.*

HANDLE ACCORDING TO GOOD SAFETY PROCEDURES AVOIDING UNNECESSARY EXPOSURE.  
STORE IN FULL CLOSED CONTAINERS AWAY FROM HEAT, LIGHT AND SOURCES OF IGNITION.  
STORE IN COOL AREA.

---

THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET WAS OBTAINED FROM CURRENT AND RELIABLE SOURCES. THIS DATA IS SUPPLIED WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY. IT IS THE USER'S RESPONSIBILITY TO DETERMINE SAFE CONDITIONS FOR USE OF THIS PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE OR EXPENSE RESULTING FROM IMPROPER USE OF THIS PRODUCT.